

USELED

Highbay

Model Cooper



Omschrijving	Waarde					
Artikel code	HB06A-50W	HB06A-100W	HB06A-150W	HB06A-200W	HB06A-300W	HB06A-400W
Afmeting in mm	600*420*52	600*420*52	600*420*52	900*420*52	1200*420*52	1500*420*52
Verbruik LED	50 watt	100 watt	150 watt	200 watt	300 watt	400 watt
Vervangt HID	125 watt	250 watt	375 watt	500 watt	750 watt	1000 watt
Lichtstroom lumen ca	8050 lm	16100 lm	24150 lm	32200 lm	48300 lm	64400 lm
Lichtopbrengst in lumen ca	7000 lm	14000 lm	21000 lm	28000 lm	42000 lm	56000 lm
Branduren	> 50.000 uur					
Power factor	> 0,95					
UGR waarde	UGR<19					
Operating Voltage	AC220-240V					
Frequency	50/60 Hz					
Type LED	Osram					
Stralingshoek	120°					
Lichtkleur	3000 / 4000K / 5000K / 6000K					
IP	54					
IK	IK10					
Cover	Transparant (T)					
Toepassing	showroom, garage, werkplaats, evenementenhal etc.					
Productgarantie	5 jaar					
Certificaten	CE, ROHS, TUV for driver					
Opties	Dimbaar, Dali					