



Omschrijving	Waarde						
	HBK-03A-30W	HBK-03A-50W	HBK-03A-60W	HBK-03A-80W	HBK-03A-100W	HBK-03A-150W	HBK-03A-200W
Artikel code							
Afmeting in mm 45°	Ø 413 * 475	Ø 413 * 475	Ø 413 * 485	Ø 413 * 495	Ø 413 * 527	Ø 413 * 559	Ø 413 * 584
Afmeting in mm 90°	Ø 413 * 315	Ø 413 * 315	Ø 413 * 325	Ø 413 * 335	Ø 413 * 355	Ø 413 * 355	Ø 413 * 355
Verbruik LED	30 watt	50 watt	60 watt	80 watt	100 watt	150 watt	200 watt
Vervangt HID	50 watt	84 watt	100 watt	150 watt	175 watt	250 watt	350 watt
Lichtstroom lumen ca	3478 lm	5797 lm	7500 lm	10000 lm	12500 lm	18500 lm	25000 lm
Lichtopbrengst in lumen ca	3025 lm	5041 lm	6050 lm	8050 lm	10050 lm	15000 lm	20000 lm
Branduren	> 50.000 uur						
Power factor	> 0,95						
Operating Voltage	AC100-240V						
Frequency	50/60 Hz						
Type LED	Philips SMD						
Stralingshoek	45° 60° 90°						
Lichtkleur	3000 - 6000K						
IP	65						
Cover	Transparant (T)						
Toepassing	showroom, garage, werkplaats, evenementenhal etc.						
Productgarantie	5 jaar						
Certificaten	CE, ROHS, TUV for driver						
Opties	Dimbaar, RGBW, Dali						